

PRODUCT SPECIFICATIONS FOR WATER DELIVERY SYSTEM FACTORY OPTION

Cannon Capacity

2,839 liters per min up to 60 meters, (750 gallons per min up to 200 ft)

Water Coverage

0.8 L/m² at speeds of 4 to 40 kph, (0.02 gal/ft² at speeds of 3 to 25 mph)

WATER DELIVERY SYSTEM FACTORY OPTION STANDARD EQUIPMENT

CONTROLS

Factory installed

Integrated into cab

Ergonomic

Durable

WATER SYSTEM MONITOR

Integrated into cab

Programmable spray configurations

Automatic diagnostic messages

VARIABLE HYDRAULIC PUMP DRIVE

1,200 gpm at speeds of 3 to 25 mph

Auto shut-off

Soft startup

STAINLESS STEEL SPRAY HEADS

Resists corrosion

Maintenance free

Patented design

INDEPENDENT HYDRAULIC & COOLING SYSTEM

Minimizes overheating

WATER CANNON

Hydraulically controlled

Optional nozzles

Integrated joystick with cab controls

Operates at idle for added fuel savings

PARTS & SERVICE

Available through global Cat Dealer Network

WATER TANK

Contact your local Cat dealer or Caterpillar OEM Solutions at oemsolutions@cat.com for assistance in obtaining water tanks through local suppliers worldwide.